
What Color is Your Existing Finish?

Light Finish Medium Finish

Dark Finish

Changing the Color of a Medium Finish







Special Walnut

If your existing finish is a medium wood tone similar to or such as <u>Minwax[®] Wood Finish™</u> colors, Colonial Maple, Gunstock, Provincial or Special Walnut, follow these tips:

• To darken your color to medium/dark brown, use PolyShades® American Chestnut or Mission Oak.



• To darken the color and add or intensify red tones, opt for PolyShades® Natural Cherry.



• PolyShades® Olde Maple and Pecan will intensify red tones without any significant darkening of the color.



• PolyShades[®] Honey Pine and Classic Oak will not have a lot of impact on the existing color, but will help cover up imperfections in an old, worn finish, while providing a layer of protection.








То

Wood Finish ™ Colonial Maple PolyShades® Classic Oak

New Color

• PolyShades[®] Bombay Mahogany and Classic Black will transform the existing finish into their respective colors.



How to Prepare Your Project

For wood previously stained with Minwax[®] Wood Finish™, but not yet finished:

- If the wood is dirty, first make sure that it's carefully cleaned with <u>Minwax[®] Wood Cabinet</u> <u>Cleaner</u> and a soft cloth.
- If the wood has been recently stained, it should NOT be cleaned as the cleaner may remove or dilute the colorants.
- If the wood has been stained but not finished, DO NOT scuff or sand. Doing so will remove the color from the edges, leaving the project looking uneven.
- Next, apply PolyShades[®].

For wood previously coated with a clear protective finish:

- Clean the existing finish with <u>Minwax[®] Wood</u> <u>Cabinet Cleaner</u> to remove dirt and grime.
- Lightly scuff the clean, dried existing finish with a synthetic sanding pad or #220-grit sandpaper.
- Use a bristle attachment on a vacuum to remove all of the dust.
- Next, apply PolyShades[®].

How to Apply PolyShades®

After the wood has been prepared according to the steps above, it's time to transform your wood with <u>PolyShades®</u>. For the best results, follow these instructions:

 Stir PolyShades[®] thoroughly, using a clean stirring stick. Gently repeat the stirring every 10 minutes to assure that the color remains evenly distributed throughout the polyurethane.



 Work quickly as you apply PolyShades[®] the length of each board in smooth, even strokes. Use the tip of your То

Minwax PolyShades Color Guide - How to Stain Over Stain | Minwax

- Using a high-quality, tapered natural bristle brush, dip only ½ to ¾ of an inch of the bristles into PolyShades[®].
- On a scrap piece of wood, practice brushing out a few strokes of PolyShades[®] to get a feel for how it flows onto the wood. Take care to apply an even coat of the product and remember: thin coats are easier to control than thick ones.

brush to gently smooth out the finish. Always apply PolyShades[®] moving your brush back and forth in the direction of the wood grain.

- As you return to the board with a freshly dipped brush, start brushing a few inches beyond where you left off, and then carefully blend the new PolyShades[®] back into the PolyShades[®] you previously applied. Doing so will help eliminate "lap marks."
- Once you have achieved an even layer of PolyShades[®], leave it alone. "Dabbing" will leave deposits of color in each spot touched by your brush. "Over-brushing" will drag the color with your bristles, resulting in an uneven application.



© 2022 Minwax® Company.